

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



INTERNATIONAL BUREAU OF PATENT COOPERATION
35, rue de la Harpe, CH-1015, Genève, Suisse
P.O. Box 6809, CH-1211, Genève, Suisse
P.O. Box 18, 2500 Leuven, Belgique
P.O. Box 17, 4800 Schiedamschen dijk, The Netherlands
P.O. Box 17, 1000 AA Amsterdam, The Netherlands
P.O. Box 17, 1000 AA Amsterdam, The Netherlands

(43) International Publication Date
13 January 2005 (13.01.2005)

PCT

(10) International Publication Number
WO 2005/003705 A1

(51) International Patent Classification⁷: G01K 11/06

(21) International Application Number:
PCT/BR2003/000061

(22) International Filing Date: 24 April 2003 (24.04.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant and

(72) Inventor: DIP, Tatiana, Maciullis [BR/BR]; Rua Estela,
67, Apto. 142, São Paulo-SP-CEP 04011-000, Brazil (BR).

(74) Agent: CRUZEIRO/NEWMARC PATENTES E MAR-
CAS LTDA; Rua Itajobi, 79, Pacaembu CEP-01246-010,
SP (BR).

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GH, GM,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK,
LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX,
MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ,
TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: INDICATIVE SENSOR FOR STOCK CONTROL



(57) Abstract: It's a device which purpose is to monitor the storage and indicate that a frozen product has been subjected to a thermal variation, with temperature rise, causing the fusion and liquefaction of a fluid (H) contained in said sensor. Said sensor comprises a hollow, cylindrical tube (2) with an open end (3), featuring a releasable cap (17) and a closed end (4), with a slidable piston (5) inside the tube (2). A compartment (C1), inside the tube (2), placed between the piston (5) and the end (4), is fulfilled with a compressed fluid (O)/spring (M), and a compartment (C2) placed between the piston (5) and the end (3), is fulfilled with said fluid (H), frozen, in the solid state. Upon the thawing of the product, the fluid (H) also taws, escaping the compartment (C2) and allowing the movement of the piston (5), pushed by the fluid (O). Said movement of the piston (5) is irreversible and constitutes the sensor's visual indication, revealing that the product has been thaw.

WO 2005/003705 A1